

- 输入电压：380V/AC/50Hz
- 合理的管路设计保证了最小的压力降
- 适用矿物冷冻机油（MO）、多元醇酯合成冷冻机油（POE）、烷基苯合成冷冻机油（AB）
- Input voltage: 380V/AC/50Hz
- Reasonable design of the tube line can make sure the minimum pressure drop
- Can be used with mineral oil (MO)、full synthetic (POE)、semi-synthetic lubricant(AB)

型号 Model	油接口尺寸 Oil connection size (\varnothing mm)	电机功率 Motor power (w)	油容积 Oil volume (l)	额定功率 (kw) (空气温度) Nominal capacity in kw (with air admission temperature)			
				27°C	32°C	36°C	43°C
FFO-025	16	90 × 1	1.3	3.5	3.2	2.9	2.5
FFO-050	22	135 × 1	1.8	7.0	6.4	5.8	5.0
FFO-100	22	230 × 1	2.7	11.0	10.5	9.5	8.0
FFO-200	28	420 × 1	3.9	17.5	16.0	14.5	12.5
FFO-300	28	550 × 1	5.2	20.5	18.5	17.0	14.0
FFO-400	28	800 × 1	7.1	31.5	28.5	26.0	22.5
FFO-500	28	550 × 2	10.4	41.0	37.0	34.0	28.0
FFO-600	28	800 × 2	14.2	63.0	57.0	52.0	45.0

以上数据基于：油进口温度：+80°C

The data listed above is on the base of the temperature of oil inlet is +80°C

型号 Model	L (mm)	L1 (mm)	A (mm)	A1 (mm)	H (mm)	图例 Fig.
FFO-025	485	420	332	252	393	a
FFO-050	568	500	332	252	444	a
FFO-100	668	600	342	252	545	a
FFO-200	775	700	442	352	647	a
FFO-300	875	800	452	352	749	a
FFO-400	1025	950	452	352	850	a
FFO-500	1625	1550	452	352	749	b
FFO-600	1925	1850	452	352	850	b

